

PROLONG F



PRODUCT DESCRIPTION

- Universal zinc plated countersunk frame anchor

PRODUCT PROMISE

Frame anchor ideally designed for hollow material

FEATURES AND BENEFITS

- ETA Approved for fastening in concrete & masonry
- Unique sleeve & expansion leg design to reach the second cavity for maximum grip in hollow material
- Different lengths & head types available
- Suitable for use in multi materials for a wide range of applications
- Easy to install

APPROVALS



APPLICATIONS

- Windows
- Doors
- Gates
- Timber frame
- Cladding

SUBSTRATES



PRODUCT RANGE

Item Description ▲▼	Drill Hole Diameter ▲▼	Anchor Length ▲▼	Min. Drilling Depth ▲▼	Max. Fixing Thickness ▲▼	First Packaging Unit (Smallest Selling Unit) ▲▼	Quantity ▲▼	Product Code ▲▼
10 x 80 / 10mm	10 mm	80 mm	80 mm	10 mm	CARDBOARD BOX	50	566653
10 x 100 / 30mm	10 mm	100 mm	80 mm	30 mm	CARDBOARD BOX	50	566654
10 x 115 / 45mm	10 mm	115 mm	80 mm	45 mm	CARDBOARD BOX	50	566655
10 x 145 / 75mm	10 mm	145 mm	80 mm	75 mm	CARDBOARD BOX	50	566656
10 x 160 / 90mm	10 mm	160 mm	80 mm	90 mm	CARDBOARD BOX	50	566657
10 x 185 / 115mm	10 mm	185 mm	80 mm	115 mm	CARDBOARD BOX	50	566658
10 x 210 / 140mm	10 mm	210 mm	80 mm	140 mm	CARDBOARD BOX	50	566659

RECOMMENDED LOADS

Anchor Length ▲▼	Anchor Shear Recommended Load Non Cracked Concrete C20/25 ▲▼	Anchor Tensile Recommended Load Non Cracked Concrete C20/25 ▲▼
80	1	1
100	1	1
115	1	1
145	1	1
160	1	1
185	1	1
210	1	1