

# Laserliner®

## ActiveFinder XP



Professional voltage testing  
of electrical wiring and systems  
– in handy pen format

Rev.0317



- **Contactless detection** of live lines from 12 V AC to 1000 V AC
- **Locates electrical voltages** in cables, sockets, bulb sockets, fuses as well as control cabinet and system components.
- **Finds breaks** in wires and cables
- **CAT IV - 1000V** – can be used for measurements throughout building installations
- **Extremely high sensitivity** for tracing lines at great depths (Zoom)
- **Clearly visible LED multi-colour signalling** for indicating electrical voltages and statuses
- Reliable status indication by additional **acoustic signalling with vibration function** even in noisy environments
- **Super-bright, integrated flashlight** with separate ON/OFF button
- **Additional LED light** for illuminating the working area
- **Compact design** with convenient clip, practical for shirt pockets and tool boxes
- Rugged, impact-resistant waterproof housing

### TECHNICAL DATA

<b>INDICATOR LED</b>
<b>VOLTAGE RANGE</b> 12 V/AC ~ 1000 V/AC Frequency 50 ... 60Hz
<b>OVERVOLTAGE CATEGORY</b> CAT IV - 1000V (non-condensing) Pollution degree 2
<b>DEGREE OF PROTECTION</b> IP67
<b>FLASHLIGHT</b> White-light LED (exempt group)
<b>POWER SUPPLY</b> 2 x 1.5 AAA (NEDA 24A/IEC LR 03)
<b>OPERATING CONDITIONS</b> 0 ... 50°C, Max. humidity 80% rH, no condensation, max. altitude 2000 m
<b>STORAGE CONDITIONS</b> -10 ... 60°C, Max. humidity 80% rH
<b>DIMENSIONS</b> (W x H x D) 160 x 24 x 30 mm
<b>WEIGHT</b> (incl. batteries) 66 g



Extremely high  
sensitivity (Zoom)

Super-bright flashlight



### ActiveFinder XP

inclusive softbag

+ batteries (2 x 1.5 AAA)

**Packing dimension** (W x H x D)

ARTICLE	ARTICLE NO	EAN-CODE	PU
ActiveFinder XP	083.013A	4 021563 698905	5

CAT IV  
1000V

2x  
AAA

IP 67

AutoSound

SOFT