

Laserliner®

CenterScanner Plus

Professional drill guide for reliable determination of entry and exit points of wall and ceiling drill holes

- Comprising a transmitter and receiver, the system facilitates straightforward alignment of the drill channel up to a wall thickness of 150 cm
- Accurate detection of the entry and exit positions by means of clearly visible LED indicators and acoustic signals
- Easily accessible marking tools "Center view" in the transmitter and receiver to determine the entry and exit positions
- Ability to calculate the required drilling **depth** up to 200 cm with the integrated LCD display
- Transmitter TX with integrated metal and voltage detection to avoid drilling holes in the wrong place
- Visual and acoustic warning when foreign objects are detected

UMAREX GmbH & Co. KG · Donnerfeld 2 · 59757 Arnsberg · Germany · Tel. +49 2932 638-300 · Fax +49 2932 638-333 · laserliner@umarex.de · www.laserliner.com

TECHNICAL DATA
CENTERSCANNER PLUS RECV
INDICATORS
13 LEDs, acoustic warning signal
LED DISPLAY 3 x 7 segment
MEASURING DEPTH
Position detection: 2–150 cm wall thickness Depth display: 2–200 cm drilling depth
ACCURACY typical 3% of measuring depth
OPERATING TIME approx. 20h
OPERATING CONDITIONS -30°C
40°C, humidity < 80%, no condensation
STORAGE CONDITIONS -40°C 60°C,
humidity < 80%, no condensation
POWER SUPPLY 3 x 1,5 V alkaline batteries (type AAA)
DIMENSIONS (W x H x D) 75 x 172 x 28 mm
WEIGHT (incl. batteries) 210 g
CENTERSCANNER PLUS TX
INDICATORS
11 LEDs, acoustic warning signal
OPERATING TIME approx. 12h
OPERATING CONDITIONS -30°C 40°C, humidity < 80%, no condensation
STORAGE CONDITIONS -40°C 60°C, humidity < 80%, no condensation
POWER SUPPLY 3 x 1,5 V alkaline batteries (type AAA)
DIMENSIONS (W x H x D) 75 x 172 x 28 mm
WEIGHT (incl. batteries) 200 g



Integrated metal and voltage detection

AutoSound TX

3x AAA





RECV 3x AAA

7			1
arking tools Center view"			
	ARTICLE NO	EAN-CODE	

ARTICLE	ARTICLE NO	EAN-CODE	PU
CenterScanner Plus	075.300A	4 021563 699926	5



CenterScanner Plus

inclusive carrying case + CenterScanner Plus RECV

- + CenterScanner Plus TX
- + Batteries
- + Adhesive kit
- + Sliding pads (4x)

Packing dimension (W x H x D) 340 x 275 x 85 mm

Rev. 0617

