

Laserliner®

SmartVision-Laser set

Rev.1016



Green cross-line laser with universal clamping bracket

SmartVision-Laser


- **Green laser technology**
- Extremely bright green laser cross at front in the **DLD design achieves high-quality lines** as well as a clean and clear and therefore easily visible line image.
- **Automatic Level:** automatic alignment by virtue of a magnetic pendulum system.
- **Individually switchable** laser lines
- **Additional slope mode** to align angled surfaces.
- **Out-Of-Level:** is indicated by optical signals when the unit is outside its self-levelling range.
- **Transport Lock:** a pendulum lock protects unit during transport.

FlexClamp Plus

- **Easy-to-adjust clamping bracket** for optimum use of cross line lasers in interior finishing applications
- **Versatile damage free mounting options** for surfaces
- **Easy-to-adjust** height and position of the measuring device
- Suitable for all laser measuring devices with 1/4" threads

TECHNICAL DATA

SELF-LEVELLING RANGE ± 5°
ACCURACY ± 0.5 mm / m
LEVELLING automatic
OPERATING RANGE (depending on room illumination) 20 m
LASER WAVELENGTH 510 nm
LASER CLASS 2 / < 1 mW
POWER SUPPLY 2 x 1.5V alkaline batteries (type AA, LR6)
OPERATING TIME 6 hours (alkaline batteries)
WORKING TEMPERATURE 0°C ... +40°C
STORAGE TEMPERATURE -10°C ... +70°C
DIMENSIONS (W x H x D) 60 x 90 x 77 mm (SmartVision-Laser)
WEIGHT (complete set) 760 g



Automatic Level



Pendulum can be locked for protection during transport



Adjustable and free mounting options



FlexClamp Plus with base support



SmartVision-Laser set

inclusive SmartVision-Laser
+ FlexClamp Plus
+ batteries

Packing dimension (W x H x D)
175 x 295 x 90 mm

ARTICLE	ARTICLE NO	EAN-CODE	PU
SmartVision-Laser set	081.336A	4 021563 698967	4

