
Laserliner®

DampMaster Compact Pro

Professional measuring device for ascertaining material moisture with the right deep-insertion electrode for every application



- Bluetooth interface for measurement data transfer
- Material groups: selection of various wood and building materials enables material-specific measurements while increasing measuring
- **LED wet/dry indicator:** 12 colour LEDs (green = dry, yellow = moist, red = wet) provide immediate measurement results for moisture content in the tested material.
- Quick localisation of moisture: comparison measurements can be made in Indicator-mode which reveal increasing or decreasing moisture based on a neutral scale.

1. Round deep-insertion electrode (non-insulated)

for moisture measurements in building and insulating materials between joints or joint

- 2. Round deep-insertion electrode (insulated) for moisture measurements in concealed material layers to assess moisture distribution in multi-layer wall or ceiling structures.
- 3. Brush deep-insertion electrode for moisture measurement in homogeneous building material without using a contact mass. Contact is established by the brush tip.
- 4. Flat deep-insertion electrode (insulated) for targeted moisture measurements in concealed material layers to assess moisture distribution in multi-layer wall or ceiling structures. Electrodes can be inserted through edge strips or at the wall-ceiling transition.

TECHNICAL DATA

MATERIALS

Wood, anhydrite screed, concrete (C12/15, C20/25, C30/37), gypsum plaster, chalky sandstone, aerated concrete, cement screed (Other materials with table in manual)

MEASUREMENT RANGE / ACCURACY

wood: 0 - 30% / ± 1%, 30 - 60% / ± 2%, 60 - 90% / ± 4% other materials: ± 0.5%

OPERATING TEMPERATURE 0 – 40°C

MAX. RELATIVE HUMIDITY 85%

PORT


Bluetooth 4.0

POWER SUPPLY

Batteries 4 x 1.5 V Typ AAA

WEIGHT 186 g

DIMENSIONS (W x H x D) 58 mm x 155 mm x 38 mm







42.B%





DampMaster Compact Pro

inclusive carrying case

- + DampExtension
- + protective cap with self-test function

Packing dimension (W x H x D) Packing dimension (W x H x D)

450 x 375 x 125 mm