PDS 5 SET



- FAST FIT: Time-saving screw tightening, four times faster than manual tightening using a conventional hand screwdriver
- COMFORT WORK: No signs of fatigue such as calluses and blisters on the palms, even after numerous screwdriving operations
- SLIM SPACE TOOL: Low space required thanks to the wedge shape. Ideal for tight workspaces that cannot be accessed with a large tool
- FINE SENSE: The manual screw tightening is perfect for finely tightening of the last turns of the screw by hand
- STANDARD NORM ADAPTER: Hexagonal bit holder with the most common size (1/4 inch/6.35 mm)
- ULTIMATE ADAPT: Suitable for many different applications due to slotted, Phillips, Pozidriv, Torx and hexagon bits
- SECURE LOCK: Reliable safety lock for a secure tool fit when drilling and when pulling the screwdriver out of the workpiece
- HIGH POWER: Powerful drive thanks to an efficient triple planetary gearbox with precision gears
- TORQUE ADJUST: Adjustable torque (1 or 5 Nm) to suit the application
- STRONG HAND LOCK: Manual tightening up to 15 Nm thanks to automatic friction-locking mechanism
- PRO POWER GRIP: Spherical handle end provides an optimal transfer of torque when turning by hand
- EASY CONTROL: Direct keys for the easy selection of clockwise or anticlockwise rotation
- AUTO LED: Integrated automatic LED illumination of the screw-fixing areas
- COMPACT SIZE: Thanks to its handy design, the device can be stored in any tool bag or box
- USB PORT: Modern USB charging technology

This versatile electric screwdriver multi-bit set has a hexagonal bit holder with the most common size (¼ inch/ 6.35 mm) and three each of slotted, Phillips, Pozidriv, Torx and hexagon bits. A practical slotted/Phillips doubleended bit is also included. A reliable safety lock ensures a secure tool fit when screwing and removing the screwdriver from the workpiece. The torque can be adjusted to 5 or 1 Newton metre. An efficient triple planetary gearbox with precision gears provides powerful drive. Tightening by hand is perfect for nipping up the last few turns of the screw. The automatic friction-locking mechanism allows up to 15 Nm to be applied manually.



Item No.	GTIN (EAN)	SU
610.500A	4021563729012	5

TECHNICAL DATA

Idle Speed	250 rpm
Torque	electric: max. 1 Nm / 5 Nm, adjustable manual: 15 Nm
Chuck	1/4" hex bits (6.35 mm) Mechanical locking type
Power Supply	USB type C 5V / 1A Li-ion battery pack 3.6V / 1.0Ah
Battery Recharging Time	approx. 70 min.

SCOPE OF DELIVERY



PDS 5, 3 x 25 mm Phillips bits (PH1, PH2, PH3), 3 x 25 mm Pozidriv bits (PZ1, PZ2, PZ3), 3 Torx bits (T10, T15, T20), 3 hexagon bits (3 mm, 4 mm, 5 mm), 3 slotted bits (0.5 x 3 mm, 0.5 x 4 mm, 0.6 x 5 mm), 2 x 75 mm Phillips bits (PH1, PH2), 1 x 75 mm double-ended bit (5 mm slotted, PH2 Phillips), Adapter from 6.35 to 4 mm, Bit holder, Suspension line, USB-C-cable, transport box