




www.prexiso-eu.com

PREXISO

- EN DIGITAL LEVEL ANGLE SLOPE
- DE DIGITALES NIVELLIERWINKEL-GEFÄLLE
- FR ANGLE DE PENTE NIVEAU NUMERIQUE
- IT LIVELLO DIGITALE DI INCLINAZIONE DELL'ANGOLO DI
- ES NIVELADOR DE ANGULO INCLINADO DIGITAL
- NL HELLENDE DIGITALE WATERPAS
- TR DİJİTAL DÜZEY AÇI EĞİMİ
- DK DIGITAL VANDRET VINKEL SKRANING
- FI DIGITAALINEN VESIVAAKA KULMAVAAKA
- NO DIGITAL NIVELLERINGSVINKELGRAD



www.prexiso-eu.com

PTD600

IMPORTANT: Read before Using EN

The safety instructions and the user manual should be read through carefully before the product is used for the first time

SAFETY INSTRUCTION:

1. Keep the instrument dry.
2. Keep the instrument and battery out of reach of infants and children.
3. When the symbol " " appears, the batteries are low and should be replaced. If you are not using the instrument for a long time, remove the battery.

Ensure that battery polarity connections are correct when replacing batteries.

PROHIBITED USE

- Using the product without instruction
- Using outside the stated limits
- Deactivation of safety systems and removal of explanatory and hazard labels
- Opening of the equipment by using tools (screwdrivers, etc.)
- Carrying out modification or conversion of the product
- Use of accessories from other manufacturers without express approval

LIMITS OF USE

Never attempt to repair the product yourself. In case of damage, contact a local dealer. Refer to section "Technical data", the device is designed for using in areas which is habitable for humans. Do not use the product in explosion hazardous areas or in aggressive environments.


AREAS OF RESPONSIBILITY RESPONSIBILITIES OF THE PERSON IN CHARGE OF THE INSTRUMENT:

- To understand the safety instructions on the product and the instructions in the User Manual.
- To be familiar with local safety regulations relating to accident prevention.
- Always prevent access to the product by unauthorized personnel.

FUNCTION

This digital level is a highly versatile leveling tool designed for fast, easy operation.

PRODUCT OVERVIEW




1. Turn on/off the device
2. Sound Function
3. Setting different angle measurements
4. Hold Function
5. Units of measurement selection (degrees, % grade, IN/FT)
6. Battery compartment(rear)
7. LCD


DISPLAY




1. Show in degrees



2. Show in percentage of grade (%)



3. Show in pitch (IN/FT)



4. Show in mm/m

OPERATION INSTRUCTIONS

1. INSERT THE BATTERY

Open battery compartment and insert two CR2032 batteries according to the installation symbols. Pay attention to the polarity while inserting the battery.



It is necessary to replace new batteries, when right corner of LCD display show " ".

2. SWITCHING ON/OFF


When the device is off, press button to turn on the device. Hold the button until the device turns off. After about 3 minutes of not using the equipment, it will automatically shut off.

3. LEVEL MEASURE

Turn on the equipment and place it on the object that needs leveling or measuring. The display will automatically show the unit of measure.

4. UNITS OF MEASUREMENT SELECTION (degrees, % grade, IN/FT, mm/m)

After switching the unit on, the screen always shows the actual slope in degrees. By pressing the (UNIT) button, you can convert angles into different units. Push to change the display units from degrees to percentage of grade (%) or to pitch (IN/FT) or to mm/m. Pitch readings are in 1/8-inch rise per foot of run increments. The icon indicates the current Angle's position, either up or down away from the horizontal or vertical position.



5. SETTING DIFFERENT ANGLE MEASUREMENTS

If the equipment isn't in a level position, it will display a value on the screen. Press the (REF) button to set the current angle to be zero; doing this the equipment will enter the reference angle measurement mode. This function allows you to set a repetitive angle. Press the (REF) button again to cancel the function.

6. SOUND FUNCTION

After the equipment is turned on, press the button and the screen will show the icon, followed by two short beeps. The sound function will beep at the horizontal or vertical position and the sound function will also beep at the predetermined angle which you set. Press the button again to cancel the sound function.

7. HOLD FUNCTION

In a position where the display might not be readable, the actual measured value can then be saved by pressing the (HOLD) button. The measurement will be frozen on the screen and the (HOLD) icon will also show on the screen. By pressing the (HOLD) button again, the measuring mode will get reactivated.

TECHNICAL DATA:

Technical specification	
Measure Range	0-360° (4×90°)
Accuracy	0° and 90°, ±0.1°; -1° to 89°, ±0.2°
Dimensions	60x3x6.2cm (23.62x1.18x2.44in)
Power supply	2xAAA alkaline batteries
Weight (without batteries)	0.65kg (1.43lb)
Working temperature	0°-40° 32°F-104°F
Storage temperature	-10°-50° 14°F-122°F

DISPOSAL



CAUTION

The battery must not be disposed with household waste. Care for the environment and take them to the collection points provided in accordance with national or local regulations. The product must not be disposed with household waste. Dispose of the product appropriately in accordance with the national regulations in force in your country. Adhere to the national and country specific regulations. Product specific treatment and waste management can be downloaded from our homepage.



WARRANTY

The Instrument PTD600 has a two-year warranty. For further information on this, contact your dealer. This warranty is void if product is used for commercial purposes. This warranty is not transferable and does not cover products damaged by misuse, neglect, accident, alterations or use and maintenance other than that specified in the owner's manual. This warranty does not apply to any expendable parts that can wear from normal use. This warranty excludes any accessories.

www.prexiso-eu.com



Prexiso AG
Fabrikstrasse 1
CH-8586 Erlen/Switzerland